

Bently Nevada 200150&200151 Series Service Manual

200150-14-05

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No.200150-14-05

Product Type : General Purpose Trendmaster 2000 or Trendmaster Pro Accelerometer

Made in U.S.A

MOunting stud option :14 = 3/8-24 to 3/8-24 UNF, 3/4 inch hex stud

Approvals : 05 = Multiple Approvals (CSA, ATEX, and IECEx)

Accelerometer 200150

Used with ProTIM Option Standard Accelerationto-Velocity channel type (-01)

Type of Application General application

Specifications

All specifications are at +25°C (+77°F), unless

otherwise specified.

Electrical

Sensitivity @

80 Hz ($\pm 12\%$)

10.2 mV/(m/s²) (100 mV/g)

Measurement Range

Accelerometer 200150

Measurement Range in m/s² (g) ± 245 (± 25)

Frequency Range Referenced to 80Hz

($\pm 10\%$)

Accelerometer 200150

Frequency Range in Hz

(cpm) 10 to 1000 (600 to 60,000)

Mounted

Resonant

Frequency

>20 kHz (>1200 kcpm)

Amplitude

Linearity

(1 to 10g pk)

$\pm 2\%$

Transverse

Sensitivity

$\leq 7\%$

Settling Time (Within 5% of Bias)

Accelerometer Settling Time (ms)

200150 ≤ 300

Excitation

Voltage

4.7 to 5.5 Vdc

Polarity

(Acceleration

from Base to

Connector)

SIG+ positive with respect to

SIG-.

Quiescent

Current

<800 μ A

Output Bias

Voltage

+2.5 $\pm$ 0.23 Vdc

Accelerometer 200150

Measurement Range in mm/s² (mg) 14.7 (1.5)

Environmental

Axial Shock

Limit

49,050 m/s² pk (5,000 g pk)

Temperature
Range
-40 °C to +105 °C (-40 °F to +221 °F)
Sealing
(Hermetic)
5X10⁻⁸ atm•cc/s (3.1X10⁻⁹ atm•in³/s), maximum
Relative Humidity
100% relative, condensing, non-submerged
Physical
Size (Hex x Height)
17.5 mm x 45.7 mm (11/16 in x 1.8 in)
Weight 58 g (2.0 oz), typical
Mounting
Thread
3/8-24 female
Mounting
Torque
2.7 to 6.8 N•m (2 to 5 ft•lbf)
Sensing
Element
Ceramic
Sensing
Geometry
Shear
Housing and connector material
200150 316L stainless steel
Temperature
Range
-55 °C to +121 °C (-67 °F to +250 °F)
Cure Time 24 hours

