

Bently Nevada 330703&330704&330705&330709&330 Series Service Manual

330709-016-240-50-02-00

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. :330709-016-240-50-02-00

Product type : 3300 XL 11 mm Proximity Probes

Made in U.S.A

330709 3300 XL 11 mm Probe, M16 x 1.5 thread, without armor

Unthreaded Length Option : 016 = 16 mm

Overall Case Length Option :240 = 240mm

Total Length Option : 50 = 5.0 meters (16.4 feet)

Five meter probes are designed for use with the five meter Proximitors Sensor only

Connector and Cable-Type Option : 02 = Miniature coaxial ClickLoc

connector, standard cable

Agency Approval Option : 00 = Not required

Probe dc Resistance

Probe Length (m) 5.0

Resistance from the Center

Conductor to the Outer

Conductor (RPROBE) (ohms)

7.2 ± 0.8

Cross-talk Limitation:

Target Size - Flat Surface

Diameter

Recommended

Minimum 30.5 mm (1.2 in)

Shaft Diameter

Recommended

Minimum 152 mm (6.0 in)

Probe Tip

Material Polyphenylene sulfide (PPS).

Probe Case

Material AISI 304 stainless steel (SST).

Probe Cable

Specification

75 Ω triaxial, fluoroethylene

propylene (FEP) insulated

probe cable in the following

total probe lengths: 1, 5 or 9

meters.

Probe Case Torque

M16x1.5 probe

cases

Maximum

Rated 63.3 N•m (560 in•lb)

Recommended 21.1 N•m (187 in•lb)

Connector-to-connector torque

Recommended

torque Finger tight

Maximum

torque 0.565 N•m (5 in•lb)

Minimum Bend

Radius (with or

without SST

armor)

25.4 mm (1.0 in)

Probe Case Thread M16x1.5

Maximum Length of Thread Engagement 24 mm

Effects of 60 Hz Magnetic Fields Up to 300

Gauss (5 meter system)

Output voltage in mil pp/gauss

Gap 0.5 mm (20mil) Probe 0.001

Gap 2.5 mm (100 mil) Probe 0.009

Gap 4.6 mm (180mil) Probe 0.027

Probe Temperature Range

Operating and

Storage

Temperature

-52°C to +177°C (-62°F to
+351°F)

Exposing the probe to temperatures
below -34°C (30°F) may cause
premature failure of the pressure
seal.

torage

Temperature

-52°C to +105°C (-62°F to
+221°F)

Relative

Humidity

100% condensing, nonsubmersible when
connectors are protected.

Tested to IEC 68-2-3 damp
heat.

Probe

Pressure

3300 XL probes are designed

to seal differential pressure

between the probe tip and

case. The probe sealing

material consists of a Viton

O-ring. Probes are not

pressure tested prior to

shipment. Contact our

custom design department if

you require a test of the

pressure seal for your

application

