

# Bently Nevada 330101 Series Service Manual

330101-00-12-10-12-00

---

## 1. Description

Manufacturer : Bently Nevada

---

## 3. Product Information



Manufacturer : Bently Nevada  
Product No. : 330101-00-12-10-12-00  
Product Type : 3300 XL 8 mm Probe, 3/8-24 UNF thread,  
without armor  
Made in U.S.A

330101 - 3300 XL 8 mm Probe, 3/8-24 UNF thread, without armor  
Unthreaded Length Option : 00 - 0.0 in  
Overall Case Length Option : 12 - 1.2 in  
Total Length Option : 10 - 1.0 metre (3.3 feet)  
Connector and Cable-Type Option : 12 Miniature coaxial ClickLoc  
connector, FluidLoc cable  
Agency Approval Option : 00 Not required

The 3300 XL probe and extension cable also  
reflect improvements over previous designs. A  
patented TipLoc molding method provides a  
more robust bond between the probe tip and  
the probe body. The probe's cable incorporates  
a patented CableLoc design that provides 330  
N (75 lbf) pull strength to more securely attach  
the probe cable and probe tip.

You can also order 3300 XL 8 mm probes and  
extension cables with an optional FluidLoc  
cable option. This option prevents oil and other  
liquids from leaking out of the machine through  
the cable's interior.

8 mm probes provide  
a thicker encapsulation  
of the probe coil in the molded PPS plastic  
probe tip. This results in  
a more rugged probe.

The larger diameter of the probe body also  
provides  
a stronger, more robust case. We  
recommend that you use  
8 mm probes when  
possible to provide optimal robustness against  
physical abuse

Nominal Probe DC Resistance  
Resistance (RPROBE) from Center Conductor  
to Outer Conductor

Probe  
Length (m)  
RPROBE(Ω)  
1.0 7.59 ± 0.50

Extension Cable  
Capacitance  
69.9 pF/m (21.3 pF/ft)  
typical

Field Wiring  
0.2 to 1.5 mm<sup>2</sup> (16 to 24  
AWG). Recommend using  
3 conductor shielded triad  
cable and tinned field  
wiring. Maximum length of  
305 meters (1,000 feet)  
between the 3300 XL

Proximitor Sensor and the  
monitor. See the frequency  
response graphs, Figures



10 and 12, for signal rolloff  
at high frequencies when  
using longer field wiring  
lengths.

#### Linear Range

2 mm (80 mils). Linear  
range begins at  
approximately 0.25 mm (10  
mils) from target and is  
from 0.25 to 2.3 mm (10 to  
90 mils) (approximately -1  
to -17 Vdc).

#### Recommended

##### Gap Setting for

##### Radial Vibration

-9 Vdc [approximately 1.27  
mm (50 mils)]

#### Incremental Scale Factor (ISF)

##### Standard 5 or 1

##### meter System

7.87 V/mm (200 mV/mil)  $\pm$   
5% including

interchangeability error  
when measured in  
increments of 0.25 mm (10  
mils) over the 80 mil linear  
range from 0°C to +45°C  
(+32°F to +113°F).

##### Standard 9

##### meter System

7.87 V/mm (200 mV/mil)  
 $\pm$  6.5% including  
interchangeability error  
when measured in  
increments of 0.25 mm (10  
mils) over the 80 mil linear  
range from 0°C to +45°C  
(+32°F to +113°F).

#### Extended

##### Temperature

##### Range (ETR) for 5

##### and 9 Meter

##### Systems

7.87 V/mm (200 mV/mil)  $\pm$   
6.5% including  
interchangeability error  
when measured in  
increments of 0.25 mm (10  
mils) over the 80 mil linear  
range from 0°C to +45°C  
(+32°F to +113°F).

#### Deviation from best fit straight line (DSL)

##### Standard 5 or 1

##### meter System

Less than  $\pm 0.025$  mm ( $\pm 1$   
mil) with components at  
0°C to +45°C (+32°F to  
+113°F).

##### Standard 9



meter System

Less than  $\pm 0.038$  mm ( $\pm 1.5$

mil) with components at

0°C to +45°C (+32°F to

+113°F).

Extended

Temperature

Range 5 and 9

meter Systems

Less than  $\pm 0.038$  mm ( $\pm 1.5$

mil) with components at

0°C to +45°C (+32°F to

+113°F).

Probe Tip

Material Polyphenylene sulfide (PPS).

Probe Case

Material

AISI 303 or 304 stainless steel

(SST).

323 g/m (11.4 oz)

Probe Temperature Range

Operating and Storage Temperature

Standard

Probe

-52°C to +177°C (-62°F to

+350°F)

Extended

Temperature

Range Probe

-52°C to +218°C (-62°F to

+425°F) for the probe tip; -

51°C to +260°C (-60°F to

+500°F) for the probe cable

and connector.

Exposing the probe to temperatures

below -34°C (-30°F) may cause

premature failure of the pressure

seal.

Probe Pressure

3300 XL 8 mm probes are designed to seal

differential pressure between the probe tip

and case. The probe sealing material consists

of a Viton® O ring. Probes are not pressure

tested prior to shipment. Contact our custom

design department if you require a test of the

pressure seal for your application.

Probe Relative Humidity

Less than a 3% change in Average Scale

Factor (ASF) when tested in 93% humidity in

accordance with IEC standard 68 2 3 for up to

56 days.

