

Bently Nevada 330101 Series Service Manual

330101-00-61-20-02-05

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. :330101-00-61-20-02-05

Product Type : 3300 XL 8 mm Probe, 3/8-24 UNF thread,
without armor

Made in U.S.A

330101 - 3300 XL 8 mm Probe, 3/8-24 UNF thread, without armor

Unthreaded Length Option :00 =0.0 in

Overall Case Length Option :61=6.1 in

Total Length Option : 20= 2.0 meters (6.6 feet)

Connector and Cable-Type Option :02= Miniature coaxial ClickLoc
connector, standard cable

Agency Approval Option

05 = CSA, ATEX, IECEx Approvals

The 3300 XL probe and extension cable also
reflect improvements over previous designs. A
patented TipLoc molding method provides a
more robust bond between the probe tip and
the probe body. The probe's cable incorporates
a patented CableLoc design that provides 330
N (75 lbf) pull strength to more securely attach
the probe cable and probe tip.

You can also order 3300 XL 8 mm probes and
extension cables with an optional FluidLoc
cable option. This option prevents oil and other
liquids from leaking out of the machine through
the cable's interior.

8 mm probes provide

a thicker encapsulation

of the probe coil in the molded PPS plastic

probe tip. This results in

a more rugged probe.

The larger diameter of the probe body also
provides

a stronger, more robust case. We

recommend that you use

8 mm probes when

possible to provide optimal robustness against

physical abuse

Nominal Probe DC Resistance

Resistance (RPROBE) from Center Conductor
to Outer Conductor

Probe

Length (m) 2.0

RPROBE(Q)

7.88 ± 0.50

Extension Cable

Capacitance

69.9 pF/m (21.3 pF/ft)

typical

Field Wiring

0.2 to 1.5 mm² (16 to 24

AWG). Recommend using

3 conductor shielded triad

cable and tinned field

wiring. Maximum length of

305 meters (1,000 feet)

between the 3300 XL

Proximito Sensor and the

monitor. See the frequency

response graphs, Figures
10 and 12, for signal rolloff
at high frequencies when
using longer field wiring
lengths.

Linear Range
2 mm (80 mils). Linear
range begins at
approximately 0.25 mm (10
mils) from target and is
from 0.25 to 2.3 mm (10 to
90 mils) (approximately -1
to -17 Vdc).

Recommended

Gap Setting for

Radial Vibration

-9 Vdc [approximately 1.27
mm (50 mils)]

Incremental Scale Factor (ISF)

Standard 5 or 1

meter System

7.87 V/mm (200 mV/mil) $\pm$
5% including

interchangeability error

when measured in

increments of 0.25 mm (10

mils) over the 80 mil linear

range from 0°C to +45°C

(+32°F to +113°F).

Standard 9

meter System

7.87 V/mm (200 mV/mil)

$\pm$ 6.5% including

interchangeability error

when measured in

increments of 0.25 mm (10

mils) over the 80 mil linear

range from 0°C to +45°C

(+32°F to +113°F).

Extended

Temperature

Range (ETR) for 5

and 9 Meter

Systems

7.87 V/mm (200 mV/mil) $\pm$

6.5% including

interchangeability error

when measured in

increments of 0.25 mm (10

mils) over the 80 mil linear

range from 0°C to +45°C

(+32°F to +113°F).

Deviation from best fit straight line (DSL)

Standard 5 or 1

meter System

Less than ± 0.025 mm (± 1

mil) with components at

0°C to +45°C (+32°F to

+113°F).

Standard 9

meter System

Less than ± 0.038 mm (± 1.5

mil) with components at

0°C to +45°C (+32°F to

+113°F).

Extended

Temperature

Range 5 and 9

meter Systems

Less than ± 0.038 mm (± 1.5

mil) with components at

0°C to +45°C (+32°F to

+113°F).

Probe Tip

Material Polyphenylene sulfide (PPS).

Probe Case

Material

AISI 303 or 304 stainless steel

(SST).

323 g/m (11.4 oz)

Probe Temperature Range

Operating and Storage Temperature

Standard

Probe

-52°C to +177°C (-62°F to

+350°F)

Extended

Temperature

Range Probe

-52°C to +218°C (-62°F to

+425°F) for the probe tip; -

51°C to +260°C (-60°F to

+500°F) for the probe cable

and connector.

Exposing the probe to temperatures

below -34°C (-30°F) may cause

premature failure of the pressure

seal.

Probe Pressure

3300 XL 8 mm probes are designed to seal

differential pressure between the probe tip

and case. The probe sealing material consists

of a Viton® O ring. Probes are not pressure

tested prior to shipment. Contact our custom

design department if you require a test of the

pressure seal for your application.

Probe Relative Humidity

Less than a 3% change in Average Scale

Factor (ASF) when tested in 93% humidity in

accordance with IEC standard 68 2 3 for up to

56 days.

Thread Engagement Limits

Probe Case Thread 3/8-24

Maximum Length of Thread Engagement

0.563 in

Probe Case Torque

Probe Type Standardforward mounted probes

Maximum Rated 33.9 N•m (300 in•lbf)

Recommended 11.2 N•m (100 in•lbf)

Probe Case Torque

Probe Type Standard forward mount probes - first three threads

Maximum Rated 22.6 N•m (200 in•lbf)

Recommended 7.5 N•m (66 in•lbf)

Temperature Schedule

(Probe Only)

For EPL Ga and Gc

Temperature Classification T1 Ambient Temperature -55°C to +232°C

Temperature Classification T2 Ambient Temperature -55°C to +177°C

Temperature Classification T3 Ambient Temperature -55°C to +120°C

Temperature Classification T4 Ambient Temperature -55°C to +80°C

Temperature Classification T5 Ambient Temperature -55°C to +40°C

For EPL Dc

Temperature Classification T280°C @ Ta Ambient Temperature -55°C to +232°C

Temperature Classification T225°C @ Ta Ambient Temperature -55°C to +177°C

Temperature Classification T170°C @ Ta Ambient Temperature -55C to +120°C

Temperature Classification T130°C @ Ta Ambient Temperature -55°C to +80°C

Temperature Classification T105°C @ Ta Ambient Temperature -55°C to +100°C

Temperature Classification T90°C @ Ta Ambient Temperature -55°C to +40°C

