

Bently Nevada 330400&330425&330500 Series Service Manual

330400-02-05

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. : 330400-02-05

Product type : Accelerometer Acceleration Transducers

Made in U.S.A

Mounting Thread Option : 0 2 M8 X 1 integral stud

Agency Approval Option :0 5

Multiple approvals (CSA, ATEX, IECEx,)

Sensitivity 10.2 mV/m/s² (100 mV/g) ±5%.

Acceleration range

490 m/s² (50 g) peak overall acceleration within the 10 Hz to 15 kHz frequency span.

Vibration at frequencies above 15 kHz, especially at the transducers resonance will significantly decrease this range.

Amplitude

Linearity

±1% to 490 m/s² (50 g) peak.

Broadband

Noise Floor

(10 Hz to 15 kHz)

0.039 m/s² (0.004 g) rms.

Frequency Response

10 Hz to 15 kHz

(600 cpm to 900,000 cpm)

±3dB;

30 Hz to 10 kHz

(1800 cpm to 600,000 cpm)

±10%

Temperature Sensitivity

-11% to +3% typical over the operating temperature range.

Transverse

Sensitivity Less than 5% of axial.

Mounted

Resonant

Frequency

Greater than 30 kHz.

Amplitude of Resonant Peak

20 dB maximum.

Base Strain Sensitivity

For serial numbers preceded by the letter "G" (including all new sensors

49 mm/s²/mstrain (0.005 g/mstrain)

For serial

numbers

NOT

preceded by

the letter "G"

(shipped

prior to April

2004)

980 mm/s²/mstrain (0.100

g/mstrain) without Mounting

Base (API adapter);

4.9 mm/s²/mstrain (0.0005

g/mstrain) with Mounting Base

(API adapter) supplied with the

accelerometer.

For units bearing

serial numbers NOT

preceded by the

letter "G", Bently

Nevada

recommends

installing with the

Mounting Base to

minimize base strain

sensitivity.

Maximum

cable length

305 metres (1000 ft) with no

degradation of signal.

Power requirements

Input

Voltage -24 ± 0.5 Vdc.

Bias Current 2 mA nominal.

Output Bias

Voltage: -8.5 ± 0.5 Vdc.

Grounding Case isolated.

Environmental Limits

Operating

and storage

temperature

-55°C to +121°C (-67°F to

+250°F)

Shock

Survivability

49,050 m/s² (5000 g) peak,

maximum.

Relative

humidity

100% condensing, nonsubmerged. Case is

hermetically sealed.

Magnetic

Field

Susceptibility

<2.21 mm/s²/gauss (225

mg/gauss) [50 gauss, 50-

60Hz].

IP Rating

Equivalent to an IP 68 (Dust

tight and watertight). Please

note that this is for the sensor

only and does not apply to the cable.

Physical

Weight (no

cable) 99 g (3.5 oz), typical

Diameter 23 mm (0.93 in).

Height 59 mm (2.3 in), including mounting stud.

Connector 3-pin MIL-C-5015 Receptacle

316L stainless steel

Mounting

Surface 32 minch rms.

Mounting

Torque 4.1 N·m (3.0 ft·lb).

Case

Material 316L stainless steel

Weight (no

cable) 100 g (3.5 oz), typical

Mounting

Angle Any orientation

