

Bently Nevada 330180&330780&330980 Series Service Manual

330780-080-00-05

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. :330780-080-00-05

Product Type : 3300 XL 11 mm Extension Cable

Made in U.S.A

Cable Length Option : 080 = 8.0 metres (26.2 feet)

Connector and Cable Option : 00 Standard cable

Agency Approval Option : 05 Multiple Approvals

Extension cable capacitance: 69.9 pF/m (21.3 pF/ft) typical

Extension Cable Material: 75 ? triaxial, fluoroethylene propylene (FEP) insulated.

Extension Cable Armor (optional): Flexible AISI 302 SST with FEP outer jacket.

Operating and Storage Temperature: -51°C to +177°C (-60°F to +351°F)

The 3300 XL 11 mm probe comes in varying probe case configurations, including armored and unarmored ½-20, 5/8 -18, M14 X 1.5 and M16 X 1.5 probe threads. The reverse mount 3300 XL 11 mm probe comes standard with either 3/8-24 or M10 X 1 threads. All components of the transducer system have gold-plated brass ClickLoc connectors. ClickLoc connectors lock into place, preventing the connection from becoming loose. The patented TipLoc molding method provides a robust bond between the probe tip and the probe body. The probe cable is securely attached to the probe tip utilizing our patented CableLoc design that provides 330 N (75 lb) pull strength. 3300 XL Probes and Extension Cables can also be ordered with a FluidLoc cable option. This option prevents oil and other liquids from leaking out of the machine through the cable's interior. The connector protector option provides additional protection of the connectors in a humid or moist environment. Connector protectors are recommended for all installations and provide increased environmental protection². Additionally, the 3300 XL 11 mm probe comes standard with a locknut with pre-drilled safety wire holes.

Notes:

1. Proximity Sensors are supplied by default from the factory calibrated to AISI 4140 steel. Calibration to other target materials is available upon request.

2. Silicone tape is also provided with each 3300 XL extension cable and can be used instead of connector protectors. Silicone tape is not recommended in applications where the probe-to-extension cable connection will be exposed to turbine oil.

Extension Cable dc Resistance

Length of

Extension

Cable (m)

Resistance

from Center

Conductor to

Center

Conductor

(RCORE)

(ohms)

Resistance

from Coaxial

Conductor to

Coaxial

Conductor

(RJACKET)

(ohms)

8.0 2.0 ± 0.5 0.6 ± 0.2

Extension cable

capacitance

69.9 pF/m (21.3 pF/ft)

typical

Field wiring

0.2 to 1.5 mm² (16 to 24

AWG) [0.25 to 0.75 mm² (18

to 23 AWG) with ferrules].

Recommend using threeconductor shielded triad

cable. Maximum length of

305 meters (1,000 feet)

between the 3300 XL

Proximito Sensor and the

monitor. See the frequency

response graph for signal

rolloff at high frequencies

when using longer field

wiring lengths.

Linear Range

4.0 mm (160 mils). Linear

range begins at

approximately 0.5 mm (20

mils) from target and is

from 0.5 to 4.5 mm (20 to

180 mils) (approximately -1

to -17 Vdc). Extended

Deviation from Straight

Line (DSL) range is from

approximately 0.5 to 5.0

mm (20 to 200 mils) (-1 to

-19 Vdc). The extended DSL

range is not applicable

when using zener barriers.

Recommended

Gap Setting 2.5 mm (100 mils)

Mechanical

Probe Tip

Material Polyphenylene sulfide (PPS).

Probe Case

Material AISI 304 stainless steel (SST).

Probe Cable

Specification

75 Ω triaxial, fluoroethylene

propylene (FEP) insulated

probe cable in the following

total probe lengths: 1, 5 or 9

meters.

Extension Cable 45 g/m (0.5 oz/ft)

Armored

Extension Cable 140 g/m (1.5 oz/ft)

Extension Cable Temperature Range

Operating and

Storage

Temperature

-52°C to +177°C (-62°F to

+351°F)

Extension Cable

Material

75 Ω triaxial, fluoroethylene

propylene (FEP) insulated.

Extension Cable

Aarmor

(optional)

Flexible AISI 302 SST with FEP

outer jacket.

CN Country Specific

