

Bently Nevada 330903&330904&330905&330910 Series Service Manual

330905-00-06-10-02-00

1. Description

Part Number:330905-00-06-10-02-00

3. Product Information

Part Number:330905-00-06-10-02-00

Model: 3300 NSv Proximity Probes

Manufacturer: Bently Nevada

Condition: New & Original in Factory Packing

Factory Warranty: 12 Months

Ordering Information

Model: 330905 - 3300 NSv Probe, M10X1 thread, without armor

Unthreaded Length Option: -00- 00 mm

Overall Case Length Option: -06-60 mm

Total Length Option: 10 1.0 meter (39 in)

Connector and Cable Type Option: 02 Miniature coaxial ClickLoc connector,
standard cable

Agency Approval Option: -00 Not required

The 3300 NSv probe and extension cable are mechanically and electrically compatible and interchangeable with Bently Nevada's previous 3300 RAM proximity probe and extension cable.

The NSv probe has increased chemical resistance compared to the 3300 RAM probe, which allows its use in many process compressor applications. The side-view characteristics of the 3300 NSv probe are also superior to those of the 3000-series 190 probe when gapping the 3300 NSv probe at the same distance from the probe target.

Probe dc Resistance

Probe Length

(m)

Resistance from the Center

Conductor to the Outer

Conductor (RPROBE)

(ohms)

1.0 4.2 ± 0.5

Extension cable

dc resistance

Center conductor: 0.220

Ω/m (0.067 Ω/ft)

Shield: 0.066 Ω/m (0.020

Ω/ft)

Extension cable

capacitance

69.9 pF/m (21.3 pF/ft)

typical

Field Wiring

0.2 to 1.5 mm² (16 to 24

AWG)[0.25 to 0.75 mm² (18

to 23 AWG) with ferrules].

Recommend using threeconductor shielded triad

cable. Maximum length of

305 meters (1,000 feet)

between the 3300 XL NSv

Proximito Sensor and the

monitor. See the frequency

response graphs Figure 16

and Figure 17 for signal

rolloff at high frequencies

when using longer field

wiring lengths.

Linear Range

1.5 mm (60 mils). Linear range begins at approximately 0.25 mm (10 mils) from target and is from 0.25 to 1.75 mm (10 to 70 mils) (approximately -1 to -13 Vdc).

Recommended

Gap Setting 1.0 mm (40 mils)

Incremental

Scale Factor (ISF)

7.87 V/mm (200 mV/mil)

+12.5%/-20% including interchangeability error when measured in increments of 0.25 mm (10 mils) over the 1.5 mm (60 mil) linear range.

Deviation from best fit straight line (DSL)

Less than ± 0.06 mm (± 2.3 mils).

Frequency Response

0 to 10 kHz: +0, -3 dB typical, with up to 305 meters (1000 feet) of field wiring.

Target Size (flat target)

Minimum: 8.9 mm (0.35 in) diameter

Recommended minimum: 13 mm (0.5 in) diameter

Axial position measurements on shaft diameters smaller than 13 mm (0.5 in) will generally result in a change in scale factor. Reducing the gap between the probe and target will help limit the change in scale factor. See Figure 12 for additional information.

Probe Tip

Material Polyphenylene sulfide (PPS).

Probe Case

Material AISI 304 stainless steel (SST).

Probe Cable

Specifications

75 Ω coaxial, fluoroethylene propylene (FEP) insulated probe cable in the following total probe lengths: 0.5, 1, 5, or 7 meters.

Recommended

torque Finger tight
Maximum torque 0.56 N•m (5 in•lb)
Minimum Bend
Radius (with or
without sst
armor)
25.4 mm (1.0 in)
Operating
Temperature
-52°C to +177°C (-62°F to
+351°F)
Storage
Temperature
-52°C to +177°C (-62°F to
+351°F)
Probe
Pressure
3300 NSv probes are
designed to seal differential
pressure between the probe
tip and case. The probe
sealing material consists of a
Viton O-ring. Probes are not
pressure tested prior to
shipment. Contact our
custom design department if
you require a test of the
pressure seal for your
application.
Connector-to-connector Torque
Probe Case
Torque
Maximum
Rated Recommended
M10X1 probe
cases – first
three
threads
22.6 N•m
(200 in•lb)
7.5 N•m
(66 in•lb)
Probe
Case
Thread
Maximum Length of Thread
Engagement
M10x1 15 mm

