

Bently Nevada 3500 Series Service Manual

3500/61-02-01

1. Description

3500/61-02-01

3. Product Information

3500/61-02-01 | Bently Nevada | Temperature Monitors

Manufacturer : Bently Nevada

Product No. : 3500/61-02-01

Product type : Temperature Monitors with Recorder Outputs

Made in U.S.A

I/O Module Type : 0 2= RTD/TC Non-isolated I/O Module

External Terminations

Agency Approval Option : 0 1= CSA/NRTL/C (Class 1, Div 2)

Specifications

Inputs

Signal Accepts from 1 to 6 RTD or TC

transducer signals.

Input

Impedance

10 MΩ for each lead input.

Power Consumption

3500/60 Nominal consumption of 7

watts.

3500/61 Nominal consumption of 9

watts.

Transducers

TCs

Type E -100 °C to +1000 °C, (-148 °F to +1832 °F).

Type J -18 °C to +760 °C, (+0 °F to +1400 °F).

Type K -18 °C to +1370 °C, (+0 °F to +2498 °F)

.Type T -160 °C to +400 °C, (-256 °F to +752 °F).

When using any of the isolated

thermocouple I/O modules (-03 or -04

I/O ordering option) with Type E

thermocouples, the available full-scale

range will be reduced if the 3500

system is operated in an ambient

temperature above +35C. The reduced

range will be -60C to +1000C (-76F to

+1832F). Rack configuration software

will allow the user to configure a

channel down to -100C but the system

will not function properly in this

scenario and therefore should not be

configured to operate with these

settings.

RTDs

100Ω 3-wire & 4-wire platinum RTD (alpha = 0.00385): -200° C to +850° C (-328 °F to +1562 °F). With external barriers: -50 °C to +850 °C (-122 °F to +1562 °F).

100Ω 3-wire & 4-wire platinum RTD (alpha = 0.00392): -200 °C to +700 °C (-328 °F to +1292 °F). With external barriers: -50 °C to +260 °C (-122 °F to + 1292 °F).

120Ω 3-wire & 4-wire nickel RTD: -80 °C to +260 °C (-112 °F to +500 °F). With external barriers: -50 °C to +260 °C (-122 °F to + 500 °F).

10Ω 3-wire & 4-wire copper RTD: -100 °C to +260 °C, (-148 °F to +500 °F). With external barriers: -50 °C to +260 °C (-122 °F to +500 °F).

Platinum RTD's with 0.00385 alphas are the worldwide industrial standard and are recommended for all applications

I/O Modules

Isolated I/O Module System Isolation: 500Vdc

Channel to Channel Isolation: 250 Vdc

Isolation is only required for fault scenarios and these

voltages will not be present on the I/O module inputs when a wiring or field fault occurs.

Outputs

Front Panel LEDs

OK LED: Indicates when the Temperature Monitor is operating properly.

TX/RX LED: Indicates then the Temperature Monitor is communicating with other modules in the 3500 rack.

Bypass LED: Indicates when the Temperature Monitor is in Bypass Mode.

RTD Current Source Value:

925 $\pm$ 15 μ A @ 25° C per transducer (single supply for the 4-wire RTD and two supplies for the 3-wire).

Recorder:

+4 to +20 mA. Values are proportional to monitor full-scale. Individual recorder values are provided for each channel. Monitor operation is unaffected by short circuits on recorder outputs.

Voltage Compliance (current output): 0 to +12 Vdc range across load. Load resistance is 0 to 600 Ω .

Resolution: 0.3662 μ A per bit $\pm$ 0.15% error at room temperature $\pm$ 0.4% error over temperature range.

Accuracy

Internal Termination NonIsolated $\pm$ 3 °C at 25 °C ($\pm$ 5.4 °F at 77 °F).

Bulkhead Rack $\pm$ 3 °C at 25 °C ($\pm$ 5.4 °F at 77 °F).

Standard Rack $\pm$ 3 °C at 25 °C ($\pm$ 5.4 °F at 77 °F).

External Termination Non-Isolated

Bulkhead Rack $\pm$ 3 °C at 25 °C ($\pm$ 5.4 °F at 77 °F).

Standard Rack $\pm$ 1 °C at 25 °C ($\pm$ 1.8 °F at 77 °F).

Internal Termination Isolated

Bulkhead Rack $\pm$ 2 °C at 25 °C

($\pm$ 3.6 °F at 77 °F).

$\pm$ 3 °C at 25 °C

$\pm$ 5.4 °F at 77 °F).

Standard Rack

$\pm$ 3 °C at 25 °C

$\pm$ 5.4 °F at 77 °F).

External Termination Isolated

Bulkhead Rack

$\pm$ 1 °C at 25 °C

($\pm$ 1.8 °F at 77 °F).

Standard Rack

°C at 25 °C

($\pm$ 1.8 °F at 77 °F)

10 Ω Copper RTDs

Resolution 1°C or 1 °F

Accuracy $\pm$ 3 °C at 25 °C

